# PLC-XU84 LCD Projector

## New Ultra-Portable LCD Projector

# PLC-XU84

- **XGA resolution**
- **2000 ANSI lumens**
- **Monitor output –** Switchable 2nd Data Input
- **Network Enabled (Ethernet & 802.11g)**
- **Auto Image Detection**
- **Flexible Lens 1.35-2.15:1**
- **Eco Mode**
- **Quick Power Off**
- **Manual Zoom & Focus**
- **Weighs only 2.6kg**

| | |
|---|---|
| Model name | PLC-XU84 |
| Panel | 0.63 inch TFT p-Si x 3 |
| No. of pixels | 1024 x 768 |
| Projection lamp | 200W UHP Lamp |
| Brightness (typical) | 2000 ANSI lumens |
| Uniformity | 85% (corner to centre) |
| Contrast ratio | 400:1 |
| Keystone Correction | ± 20° vertical |
| Projection lens<br>Throw ratio<br>Screen size | F 1.65 – 2.5, f=17.7 – 28.3mm<br>1.35 – 2.15:1<br>40”-300” |
| AV Signal | Input: Composite (RCA), Component(D-Sub15), S-Video(DIN4)<br>Stereo (RCAx2) |
| Color systems | PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N |
| PC Signal | Input: DVI-I<br>Audio input: Mini-Jack (Stereo) for Computer Input<br>Audio output: Mini-Jack (Stereo) variable output<br>Output: RGB (D-Sub15), switchable 2nd data input |
| Control Port | Serial x 1 (RS-232C), USB type B x 1 |
| Computer compatibility | UXGA/ SXGA/ XGA/ SVGA/ VGA/ MAC |
| Scanning frequency | H-sync 15-100kHz, V-sync 50-100Hz, Dot Clock 140MHz |
| Sound output | 1.0W mono |
| Voltage | 100V-240V AC (auto voltage) |
| Dimensions(W x H x D) | 295 x 70 x 208 mm |
| Weight | 2.6kg |

Specifications subject to change without notice